Declaration of Performance

Gyproc Sealant

SEAL100

1. Unique identification code of the produc	t-type:
	Gyproc Sealant
Type, batch or serial number or any other or product as required pursuant to Article 11(4)	element allowing identification of the construction 4):
	Gyproc Sealant
2. Intended use/es:	
	F-INT Acrylic Sealant and adhesive used for sealing small air gaps
3. Manufacturer:	
	British Gypsum
	Registered in England 734396
	East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
4. Authorised representative:	
	N/A
5. System/s of AVCP:	
	System 4 generally
6a. Harmonised standard:	BS EN 15651-1: 2012
	B3 EN 13031-1. 2012
Notified body/ies:	N/A
	.,,,,



6b. European Assessment Document:	N/A
European Technical Assessment:	.,,,
Tanksiaal Assassmant Radiu	N/A
Technical Assessment Body:	N/A
Notified body/ies:	
	N/A

7. Declared performance/s:

The characteristics in the table below apply to all products mentioned in 2 above.

Essential Characteristics	Performance	Harmonised technical specification		
Reaction to Fire (R2F)	F	BS EN 15651-1: 2012		
Water tightness and air-tightness determined by:				
Resistance to flow	≤5mm	BS EN 15651-1: 2012		
Loss of volume	≤45%	BS EN 15651-1: 2012		
Tensile properties: Elongation at break at 23°C	≥25%	BS EN 15651-1: 2012		
Durability	Pass	BS EN 15651-1: 2012		

8. Appropriate Technical Documentation and / or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Alastair Bell, Managing Director British Gypsum

Madabell

East Leake 01/04/2017

(Signature) (Place and date of issue)

