











ADAFASTFIX
DRYLINING & CONSTRUCTION SUPPLIES

APPLICATION GUIDE

ETICS, SOFFIT & DRY LININGS APPLICATIONS







Kingspan Product	Kingspan product description	EJOT CODE	APPLICATION	EMBEDMENT	pilot hole dia mm	LENGTH/MATERIAL
K5EWB	External wall board for ETICS.	 TID.T 8/60 X L	To solid brickwork or concrete.	35mm	8mm	polypropylene body with plastic headed zinc plated carbon steel pin: 75 to 260mm.
K5EWB	External wall board for ETICS.	 SBH-T WASHER + SW8-R fastener	To steel stud 0.7-1.2mm or plywood or some grade of OSB or some types of cement particle boards	40mm to timber 20mm Protrusion from plywood		Polyamide capped washer with climadur coated carbon steel fastener SW8R 4.8 x 60 - SW8R 4.8 x 220.
K10	Soffit insulation board with foil face.	 DDS with DDT70 washer	To dense concrete soffit	20mm	6mm	Zinc plated hardend carbon steel anchor with intergal 25mm dia plastic washer face DDS 7.3 x 50 - 220. DDT 70, 70mm dia galvanised steel washer.
K10	Soffit insulation board calcium silicate board.	 DDS	To dense concrete soffit	20mm	6mm	Zinc plated hardend carbon steel anchor with intergal 25mm dia plastic washer face DDS 7.3 x 50 - 220.
K10	Soffit insulation board with foil face.	 JT3-D6H fastener + DDT70 washer	To steel 1.5mm to 6.0mm thick			JT3-D6H 5.5/6.3 x L stainless steel Bi-Met fastener with DDT70 70mm dia galvanised steel spreader washer.
K10	Soffit insulation board calcium silicate board.	 JT3-D6H fastener + HTV40SS washer	To steel 1.5mm to 6.0mm thick			JT3-D6H 5.5/6.3 x L stainless steel Bi-Met fastener with HTV40SS 40mm dia stainless steel spreader washer.
K10	Soffit insulation board with foil face.	 JT3-D12H fastener + DDT70 washer	To steel 4.0mm to 12.0mm thick			JT3-D12H 5.5/6.3 x L stainless steel Bi-Met fastener with DDT70 70mm dia galvanised steel spreader washer.
K10	Soffit insulation board calcium silicate board.	 JT3-D12H fastener + HTV40SS washer	To steel 4.0mm to 12.0mm thick			JT3-D12H 5.5/6.3 x L stainless steel Bi-Met fastener with HTV40SS 40mm dia stainless steel spreader washer.

ISSUE 3 2010 Page 1 of 2

ADA Fastfix
Unit 10 Merlin Centre
High Wycombe
Buckinghamshire
HP12 3QL

01494 478 478
info@adafastfix.co.uk



Kingspan Product	Kingspan product description	EJOT CODE	APPLICATION	EMBEDMENT	pilot hole dia mm	LENGTH/MATERIAL
K10	Soffit insulation board with foil face.	JT3-D6H fastener + DDT70 washer 	To timber substrate.	40mm		JT3-D6H 5.5/6.3 x L stainless steel Bi-Met fastener with DDT70 70mm dia galvanised steel spreader washer.
K10	Soffit insulation board calcium silicate board.	JT3-D6H fastener + HTV40SS washer 	To timber substrate.	40mm		JT3-D6H 5.5/6.3 x L stainless steel Bi-Met fastener with HTV40SS 40mm dia stainless steel spreader washer.
TW53	Insulation for ETICS to traditional and light weight renders.	 TID.T 8/60 X L	To solid brickwork or concrete.	35mm	8mm	poypropylene body with plastic headed zinc plated carbon steel pin: 75 to 260mm.
TW53	Insulation for ETICS to traditional and light weight renders.	 SBH-T WASHER + SW8-R fastener	To steel stud 0.7-1.2mm or plywood or some grade of OSB or some types of cement particle boards	40mm to timber 20mm Protrusion from plywood		Polyamide capped washer with climadur coated carbon steel fastener SW8R 4.8 x 60 - SW8R 4.8 x 220.



EJOT U.K. LTD

Tel/Fax: 01977 68 70 40/01977 68 70 41

www.ejot.co.uk

see EJOT Building Fastener Catalogue for more details.

