











ADAFSTFIX
DRYLINING & CONSTRUCTION SUPPLIES

Kooltherm® K10 Soffit Board

Kingspan Kooltherm achieves an A+ BRE Green Guide rating

Kingspan Product	Kingspan product description	EJOT CODE	APPLICATION	EMBEDMENT	pilot hole dia mm	LENGTH/MATERIAL
K10	Soffit insulation board with foil face.	DDS with DDT70 washer 	To dense concrete soffit	20mm	6mm	Zinc plated hardend carbon steel anchor with intergal 25mm dia plastic washer face DDS 7.3 x 50 - 220. DDT 70, 70mm dia galvanised steel washer.
K10	Soffit insulation board calcium silicate board.	DDS 	To dense concrete soffit	20mm	6mm	Zinc plated hardend carbon steel anchor with intergal 25mm dia plastic washer face DDS 7.3 x 50 - 220.
K10	Soffit insulation board with foil face.	JT3-D6H fastener + DDT70 washer 	To steel 1.5mm to 6.0mm thick			JT3-D6H 5.5/6.3 x L stainless steel Bi-Met fastener with DDT70 70mm dia galvanised steel spreader washer.
K10	Soffit insulation board calcium silicate board.	JT3-D6H fastener + HTV40SS washer 	To steel 1.5mm to 6.0mm thick			JT3-D6H 5.5/6.3 x L stainless steel Bi-Met fastener with HTV40SS 40mm dia stainless steel spreader washer.
K10	Soffit insulation board with foil face.	JT3-D12H fastener + DDT70 washer 	To steel 4.0mm to 12.0mm thick			JT3-D6H 5.5/6.3 x L stainless steel Bi-Met fastener with DDT70 70mm dia galvanised steel spreader washer.
K10	Soffit insulation board calcium silicate board.	JT3-D12H fastener + HTV40SS washer 	To steel 4.0mm to 12.0mm thick			JT3-D6H 5.5/6.3 x L stainless steel Bi-Met fastener with HTV40SS 40mm dia stainless steel spreader washer.
K10	Soffit insulation board with foil face.	JT3-D6H fastener + DDT70 washer 	To Timber substrate	40mm to timber 20mm Protrusion from plywood		JT3-D12H 5.5/6.3 x L stainless steel Bi-Met fastener with DDT70 70mm dia galvanised steel spreader washer.
K10	Soffit insulation board calcium silicate board.	JT3-D6H fastener + HTV40SS washer 	To Timber substrate	40mm to timber 20mm Protrusion from plywood		JT3-D12H 5.5/6.3 x L stainless steel Bi-Met fastener with HTV40SS 40mm dia stainless steel spreader washer.

ISSUE 3 2010 Page 1 of 1

ADA Fastfix
Unit 10 Merlin Centre
High Wycombe
Buckinghamshire
HP12 3QL

01494 478 478
info@adafastfix.co.uk

