FABRI[™]



FABRI™ sports a single-piece frameless design with self-adjusting TempFLEX™ temple tips.

Exceptional value in a lightweight frame.

SPECIAL FEATURES

- Single wraparound polycarbonate lens
- ✓ Universal nose bridge
- Flexible temple tips
- **V** UV400 protection
- Supplied with neck cord
- Weight: 22g
- 9.75-Base lens









VERSIONS		REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS	
CLEAR	0	RLY00191	2C-1.2 € 1FT C €	€ EN 166 FT C €	Impacts, UV radiations	A - P I - I	
GREY		RLY00192	5-2.5 € 1FT C €	€ EN 166 FT C €	Impacts, UV and Solar radiations	Anti-scratch	

See overleaf for this product's technical specification>

FABRI™



GENERAL SPECIFICATION

LENS BASE	9.75mm
WEIGHT	22g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	One piece moulded lens
NOSE BRIDGE	Polycarbonate	One piece moulded universal
TEMPLE	Thermoplastic Elastomers (TPE)	Flexible and comfortable
HINGE	Metal	Hard wearing

LENS MARKINGS

LENS FILTER TYPE:

2C UV

5 Solar

SCALE NUMBER (SHADE):

1.2 Clear or Amber

2.5 Grey

@ Identity of the manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures

C€ Certification mark

FRAME MARKINGS

C Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86 g ball at 45 m/s
- T Protection against high-speed particles at extreme temperatures

C€ Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the

complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

