

**EVERBUILD FIRESPAN INTUMESCENT PADS**

Colour	Product Code	Pack Size	Box Qty
Red	FSPANSNGL	SINGLE	20
Red	FSPANDBLE	DOUBLE	20

**Product Description**

EVERBUILD FIRESPAN INTUMESCENT PADS are pre-cut intumescent pads designed for easy application around single and double electrical socket installations. Tested in accordance with EN1366-3, FIRESPAN INTUMESCENT PADS provide up to 2 hours fire protection in certain configurations (Warrington Test Report No.) Acoustic rated to BS EN ISO 140/3. Tested for air permeability to EN13141-1 Ventilation for buildings. Performance testing of components/products for residential ventilation.

Available in two sizes 230mm x 170mm x 4mm and 170 x 170mm x 4mm FIRESPAN INTUMESCENT PADS fit most common light socket boxes or 13amp ring main sockets either internally or externally.

**Benefits**

- Maintains a fire and smoke barrier around sockets in drylining systems.
- Excellent Acoustic properties.
- Tested to EN 1366-3 to provide up to 2 hours fire protection.
- High tack adhesion, pliable and mouldable with excellent self bonding properties.
- Preformed shape to fit most common socket boxes

**Areas For Use**

- Dry Lining systems
- Around metal or plastic socket boxes.
- Fire rated partition walls.

**Limitations**

- Do not use in areas where a fire rating in excess of 2 hours is required.
- Do not use in areas subject to prolonged high temperatures i.e. central heating pipes, ducting etc.
- It is the users responsibility to determine suitability for use however if in doubt contact Technical Services for advice.

**Surface Preparation**

All surfaces must be clean, dry and free from any loose dust or contaminants. Do not apply to damp surfaces.

### Application

FIRES PAN INTUMESCENT PADS fit either internally or externally on the back of electrical boxes. Remove the lining paper from the pad. When using internally fold the pad to the shape of the box first then press home firmly into the box working into the back and corners.

When using externally, fold the pad around the back and sides of the socket when in situ. Press the edges of the pad together to form a continuous seal around the box. Ensure edges are brought firmly together to ensure complete coverage.

### Specific Data

Specific Gravity	1.55-1.60 g/cm <sup>2</sup>
Consistency	Stiff Putty
Intumescent Temperature	Approx 250°C
Composition	Silicone Rubber Polymer Containing intumescent Fillers – red colour
Integrity /insulation	2 hours*

\*up to 2 hour fire rating in certain configurations. Refer to Warrington Fire Report No. for full details.

### Health & Safety

Consult MSDS for full list of hazards

### Storage

Store in cool dry conditions away from direct sunlight.

### Shelf Life

36 months from date of manufacture in original wrapper.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*