TECHNICAL INFORMATION FOR

COLLATED DRYWALL SCREWS FINE THREAD





DRYWALL SCREWS - FINE THREAD



 Used to secure plasterboard to drywall track and ceiling track systems (Max 0.7mm)











PLASTERBOARD THIN METAL

FEATURES




- Phillips No.2 recess for a positive drive.
- Bugle head to reduce likelihood of damaging the board surface.
- Thread offers excellent pull out values and insertion speed into a maximum of 0.7mm steel.
- 60° twinthread offers excellent pull out values and insertion speed.
- 25° 'Super Sharp' point for ease of penetration.
- Plated in a BZP (Bright Zinc Plate) or Black Phosphate to withstand over 50hrs salt spray. Tested in accordance with ASTM B117-11.
- Manufactured from a hardened durable C1018 carbon steel, offering excellent strength and ductility.
- Full batch traceability.

PRODUCT RANGE

ZINC

Product Code	Size (mm)	Box Qty	Carton Qty (Box)	Carton Qty	Pallet Qty (Box)	Pallet Qty
00025COLDZYS	3.5 x 25	1,000	10	10,000	320	320,000
00032COLDZYS	3.5 x 32	1,000	10	10,000	320	320,000
00035COLDZYS	3.5 x 35	1,000	10	10,000	320	320,000
00038COLDZYS	3.5 x 38	1,000	10	10,000	240	240,000
00042COLDZYS	3.5 x 42	1,000	10	10,000	240	240,000
00050COLDZYS	3.5 x 50	1,000	10	10,000	240	240,000
00055COLDZYS	3.5 x 55	1,000	10	10,000	240	240,000

INSTALLATION GUIDELINES



In order to guarantee a secure fixing, the screw must fully penetrate and pertrude through the back of the steel by a minimum of 10mm


DIMENSIONS


Product Code	DK (mm)	L (mm)	d (mm)	D (mm)	TI (mm)	Max Drill Thickness (mm)
00025COLDZYS	8.15	25.0	2.15	3.50	18.0	0.7
00032COLDZYS	8.15	32.0	2.15	3.50	25.0	0.7
00035COLDZYS	8.15	35.0	2.15	3.50	31.0	0.7
00038COLDZYS	8.15	38.0	2.15	3.50	35.0	0.7
00042COLDZYS	8.15	42.0	2.15	3.50	38.0	0.7
00050COLDZYS	8.15	50.0	2.15	3.50	43.0	0.7
00055COLDZYS	8.15	55.0	2.15	3.50	50.0	0.7

*all figures stated are approximate and for reference only.

DK	Head Diameter
L	Length
TI	Thread Length

d	Minor diameter
D	Major Diameter





COLLATED STRIP



FEATURES

- Light density polyethylene (LDPE) material
- Unique yellow colour
- Tight tolerances to ensure universal compatibility
- 50 screws per strip (wide choice available)