

product datasheet

vertical flange clip



www.evolutionfasteners.co.uk



Designed for:	Fixing lighting or suspended wire to steel profiles, cable to 1.6mm - 2.5mm thick steel purlins or suspended ceilings to steel profiles.
Product Code:	VFC43
Size:	19mm x 43mm
Coating:	Yellow zinc passivated
Shank Material:	Carbon steel
Material Grade:	AISI C1022
Fire Tested:	Yes, to EN1364-1 <small>(ask for details of our fire test results for more information)</small>
Box Qty:	100
Carton Qty:	1,800

Evolution Fasteners (UK) Ltd
 Unit 2A & 2B
 Clyde Gateway Trade Park
 Dalmarnock Road
 Rutherglen
 Glasgow
 G73 1AE
 Tel: +44 (0)141 647 7100
 Fax: +44 (0)141 647 5100
technical@evolutionfasteners.co.uk

Recommended Working Loads	
Ultimate Load	Recommended Load*
0.74kN	0.19kN

* This recommended load has been calculated where the clip is not fixed by a self drilling screw. When fixed with a self drilling wafer head screw, higher tensile values can be achieved. We recommend that site testing is undertaken to calculate an accurate recommended load.

Application Guide

1. Place hook profile over the vertical of the purlin
2. Tap into place with a hammer
3. We recommend using a wafer head self-drilling screw to secure the clip (Evolution WHSDZ12)
4. Connect drop wires or chains through the eye of the clip

Ask for Evolution



Drywall Screws



Tek Screws




Collated Screws



Masonry Screws



Anchors



Clips & Brackets

NOTE: The results expressed in the datasheet are taken as mean loads from a range of empirical tests and are ultimate unfactored loads. Each specifier or end user should make his/ her own decision on what safety factors to use relevant to their design application (such as BS 5950, EN 1991, etc).

Errors and Omissions Excepted.