


















ROCKWOOL APPLICATION GUIDE

Rockwool Product	EJOT CODE	APPLICATION	EMBEDMENT & DRIVE BIT	Hole Dia	LENGTH/MATERIAL
Rainscreen Duo-slab	Insulation support anchor DH-2 Piece 	Fixing insulation board to masonry. Perimeter fixing.	20-30mm Hammer set fix	8mm	DH 8 x 60,80,100-180mm Polyethylene Shaft used with DH90 Disc
Rainscreen Duo-slab	DMH-8 x L (E) with  DMT 80 (E) Washer 	Fixing insulation board to masonry. Centre fixing.	50-80mm Hammer set fix	8mm	DMH-8 x 80,110,140,170,200,250,300 (E) A2 stainless steel to be used with 80mm A2 stainless steel washer.
Rainscreen Duo-slab	SW8R 4.8 x L   with SBV 90 washer 	Fixing insulation board to sheathing panel and steel stud, perimeter fixing.	Protrusion from sheathing board - 20mm 8mm Hexagon		SW8R-4.8x 60,80,90,100 - 260. Organic coated carbon steel. SBV 90, glass reinforced nylon tube washer.
Rainscreen Duo-slab	JT3-D6H 5.5/6.3 x L with  DMT 85-7 E  	Fixing insulation board to sheathing panel and steel stud, centre fixing.	Protrusion from sheathing board - 20mm 8mm Hexagon		JT3-D6H 5.5/6.3 x 67,87,107,127,147,167,197 and 237. A2 stainless steel bi-metal to be used with 85mm A2 stainless steel washer.
Soffit Liner	DDS 7.3 x L   + DDT70 washer 	Fixing soffit board to concrete.	20mm TORX 30	6mm	DDS 7.3 x 100,125,150,175 and 200. Hardened carbon steel drive screw with integral plastic washer face with DDT70 70mm diameter galvanised steel washer.
Soffit Liner	JT3-D6H 5.5/6.3 x L   + DDT70 washer 	Fixing soffit board to 1.5mm to 3.0mm steel.	Different on application 8mm Hexagon		JT3-D6H 5.5/6.3 x 67,87,107,127,147,167,197 and 237. A2 stainless steel bi-metal to be used with DDT70 70mm diameter galvanised steel washer.







ADA Fastfix

Unit 10 Merlin Centre
High Wycombe
HP12 3QL
Tel: 01494 478 478
Email: info@adafastfix.co.uk

www.adafastfix.co.uk



ROCKWOOL APPLICATION GUIDE

Rockwool Product	EJOT CODE	APPLICATION	EMBEDMENT & DRIVE BIT	Hole Dia	LENGTH/MATERIAL
Duo Rock Roofing Boards and Hardrock	HTK 2G 50 x L Tube washer with TKR 4.8 x L 	Fixing insulation board to 0.7mm to 1.2mm steel and timber. HTK 2G 50 x L is for fixing mechanically.	Protrusion from deck - 20mm P2 Phillips		HTK 50-15, 35, 55, 95 and 145 Polyamide tube washer. TKR 4.8 x 50,60,80 to 140 organic coated carbon
Duo Rock Roofing Boards and Hardrock	HTK 2G 75 x L Tube washer with TKR 4.8 x L 	Fixing insulation board to 0.7mm to 1.2mm steel and timber. For fixing adhered membrane.	Protrusion from deck - 20mm P2 Phillips		HTK 50-15, 35, 55, 95 and 145 Polyamide tube washer. TKR 4.8 x 50,60,80 to 140 Organic coated carbon steel.
Duo Rock Roofing Boards and Hardrock	EcoTek with FBS-R 	Fixing insulation board to dense concrete.	FBS-R 30mm EMB TORX 30	5.0mm	EcoTek tube, Polyethylene with FBS-R 6.3- case hardened carbon steel.
Duo Rock Roofing Boards and Hardrock	EcoTek with FPS-E 	Aerated concrete	FPS-E 60mm EMB. TORX 30	No pilot hole	EcoTek tube, Polyethylene with FPS-E 8.0- A4 stainless steel.
Fire Barrier	4H - 6.3 x L 	Fixing Fire barrier support angle via a punched strap to concrete.	25-35mm 8mm Hexagon	5.0mm	4 H 6.3 x 32,45, Hardened zinc plated carbon steel anchor.
Fire Barrier	4H SS 7.5 x L 	Fixing Fire barrier support angle via a punched strap to concrete.	25-35mm 10mm Hexagon	6.0mm	4 H 7.5 x 45 Stainless steel 'tapcon'

ADA Fastfix

Unit 10 Merlin Centre
High Wycombe
HP12 3QL
Tel: 01494 478 478
Email: info@adafastfix.co.uk

www.adafastfix.co.uk